



Bentonite Mud Mixer Model M-750L

Surface to Surface Inc.



Features and Benefits

M-750L Mixer

The M-750L was designed and manufactured to provide the same fast and efficient Bentonite mixing as the standard M-750, but with an alternative footprint for special applications. The longer, narrower footprint allows the Contractor the option of mounting the unit to one side of a 96 inch platform, while allowing a 31 inch walkway and work area in front of the mixer (Gas Model). Also available with an optional 23.5 hp liquid cooled diesel engine (Larger Footprint).



Specifications

- Dimensions
- Weight
- Hopper Height
- Mixing System
- Mixing Tank
- Skid Frame
- Engine
- Pump
- Pump Drive
- Fuel Tank
- Pipe Couplers
- Pressure Wand
- Tank Drain

M-750L Mixer

- 65" W x 116.5" L x 75" H
- 1900 Lbs
- 39" High
- 4" Patented StS Mixing System
- 750 gal. Roto-Molded polyethylene
- 5" Steel channel, welded
- 18.0 hp air-cooled, electric start
- 4" Cast iron centrifugal trash pump
- Direct coupled engine to pump
- 15 gal. Steel c/w sight gauge
- Bolt & Snap-groove type
- Hopper maintenance wand
- Bottom tank drain supplied

Benefits

- The long design allows for alternative placement by the contractor.
- Waist high hopper reduces back strain.
- Fast, efficient mixing time (8 min. mix).
- Minimal maintenance required.
- Built for the rigors of the construction trade.
- Industrial rated for long service life.
- Rugged & repairable for extended service life.
- No expensive couplers or inserts to replace.
- Provides a full day running on a fill up.
- Provides fast cold weather draining of system.
- Removal of blockages caused by additives.
- Provides fast cold weather tank drainage.

*** All Specifications Subject to Change Without Notice ***

Check our website for the latest products and specifications
www.stswm.com info@stswm.com

Surface to Surface Inc.

5150 Forest Road, R.R.#3, Watford, Ontario, N0M 2S0
Tel: 1-800-567-0978

04/12/07