



Bentonite Mud Mixer Model M-750LD

Surface to Surface Inc.



Features and Benefits

M-750LD Mixer

The M-750LD was designed and manufactured to provide the same fast and efficient Bentonite mixing as the standard M-750, but with an alternative footprint for special applications and a 23.5 hp liquid cooled diesel engine. The longer, narrower footprint allows the Contractor the option of mounting the unit to one side of a 96 inch platform, while allowing a walkway and work area in front of the mixer. Also available with an optional 18 hp gas engine (Smaller Footprint).



Specifications

M-750LD Mixer

Dimensions	73.5" W x 116.5" L x 75" H
Weight	2400 Lbs
Hopper Height	39" High
Mixing System	4" Patented StS Mixing System
Mixing Tank	750 gal. Roto-Molded polyethylene
Skid Frame	5" Steel channel, welded
Engine	23.5 hp water-cooled Diesel
Pump	4" Cast iron centrifugal trash pump
Pump Drive	Direct coupled engine to pump
Fuel Tank	15 gal. Steel c/w sight gauge
Pipe Couplers	Bolt & Snap-groove type
Pressure Wand	Hopper maintenance wand
Tank Drain	Bottom tank drain supplied

Benefits

- The long design allows for alternative placement by the contractor.
- Waist high hopper reduces back strain.
- Fast, efficient mixing time (8 min. mix).
- Minimal maintenance required.
- Built for the rigors of the construction trade.
- Industrial rated for long service life.
- Rugged & repairable for extended service life.
- No expensive couplers or inserts to replace.
- Provides a full day running on a fill up.
- Provides fast cold weather draining of system.
- Removal of blockages caused by additives.
- Provides fast cold weather tank drainage.

*** All Specifications Subject to Change Without Notice ***

Check our website for the latest products and specifications
www.stswm.com info@stswm.com

Surface to Surface Inc.

5150 Forest Road, R.R.#3, Watford, Ontario, N0M 2S0
Tel: 1-800-567-0978

04/12/07